

## *Equipment Specifications*

<b>Fisher Model</b>	<b>Tank Capacity</b>	<b>Tank Size</b>	<b>Overall Size</b>	<b>Weight</b>	<b>Ultra Sonic Power</b>	<b>Heater Power</b>	<b>Total Power (MTH)</b>
FS-20	3/4 gal. (2.8 L)	L: 6" W: 5.5" D: 6"	L: 8.9" W: 8.9" H: 11.3"	11 lbs. (5KG)	80W	63W	80W 63W 143W
FS-30	1 gal. (3.7 L)	L: 9.5" W: 5.5" D: 6"	L: 10.4" W: 8.9" H: 11.3"	13 lbs. (5.9 KG)	130W	109W	130W 109W 239W
FS-60	1-1/2 gal. (5.7 L)	L: 11.5"  W: 6" D: 6"	L: 12.7" W: 9.5" H: 11.3"	15 lbs. (6.8 KG)	130W	205W	130W 205W 335W
FS-110	2-1/2 gal. (9.5 L)	L: 11.5" W: 9.5" D: 6"	L: 12.7" W: 13" H: 11.3"	19 lbs. (8.6 KG)	185W	284W	185W 284W 469W
FS-140	3-1/2 gal. (13.3 L.)	L: 11.5" W: 9.5" D: 8"	L: 12.7" W: 13" H: 13.3"	20lbs. (9.1 KG)	185W	284W	210W 284W 469W
FS-220	5-1/2 gal. (20.8 L)	L: 19.5" W: 11.5" D: 6"	L: 21.4" W: 15.4" H: 11.3"	32 lbs. (14.5 KG)	320W	561W	320W 561W 881W

### **NOTE:**

- All models have an operating frequency of 40kHz.
- Voltages available: 120V or 220V ± 10%, 50/60Hz (Check your label)
- All cleaners have CSA approval and comply with FCC regulations.
- All 220V units meet CE standards.
- Units will cause GFI outlets to trip.
- All units have a ground leakage current less than .50ma.