


VWR Galaxy* D Microcentrifuges

PREVIOUS NEXT



- Digital Controls and Display
- Quiet and Cool Running
- Cold Room Compatible
- Small and Easily Transported

The advanced technology and streamlined design of the Galaxy line deliver optimum performance in a compact unit. All parameters, including rpm, RCF, and time, are set and displayed digitally. Galaxy Digital Microcentrifuges accelerate quickly to the set speed and employ dynamically controlled braking to come to a soft stop without disrupting fragile samples. All models come with a fixed angle microtube rotor. All rotors are supplied with a snap-on rotor cover and are easily removed for cleaning and autoclaving. Galaxy microcentrifuges have a small footprint, are easily transported, and are safe for cold room use.

	Galaxy 5D	Galaxy 7D	Galaxy 14D	Galaxy 16D	Galaxy 16DH
Maximum Speed:	8,500 rpm	10,000 rpm	13,000 rpm	14,000 rpm	13,300 rpm
Maximum RCF:	5,200 g	7,200 g	14,000 g	16,000 g	16,000 g
Capacity:	12 x 1.5/2.0 mL	12 x 1.5/2.0 mL	18 x 1.5/2.0 mL	18 x 1.5/2.0 mL	24 x 1.5/2.0 mL
Timer:	15 minutes	99 minutes	99 minutes	99 minutes	99 minutes
Dimensions:	19.7 x 17.8 x 12.7 cm	19.7 x 17.8 x 12.7 cm	26.7 x 23.8 x 17.8 cm	26.7 x 23.8 x 17.8 cm	26.7 x 23.8 x 17.8 cm
	7 ³ / ₄ x 7 x 5"	7 ³ / ₄ x 7 x 5"	10 ¹ / ₂ x 9 ³ / ₈ x 7"	10 ¹ / ₂ x 9 ³ / ₈ x 7"	10 ¹ / ₂ x 9 ³ / ₈ x 7"
Weight:	3.25 lbs. (1.5 kg)	3.25 lbs. (1.5 kg)	11 lbs. (5.0 kg)	11 lbs. (5.0 kg)	11.75 lbs. (5.3 kg)
Electrical:	120V, 50/60 Hz	120V, 50/60Hz	120V, 50/60Hz	120V, 50/60Hz	120V, 50/60Hz